

The STS 6004 Programmable Automated Fuel Maintenance System is designed to optimize and maintain diesel fuel indefinitely. Adding an STS 6004 system will remove particulate, separate water, and condition the fuel. This innovative process stabilizes diesel and bio-fuels, eliminates microbial contamination, and ensures clean reliable fuel at all times. Generators and pumps operating in remote locations are ideal applications for STS 6004 systems.



STS 6000 SERIES SAFETY FEATURES:

- **Automatic Alerts**
- Pump Shut Down When Filters Need Service
- Leak Detection
- Water Detection
- High Filter Vacuum
- High Pump Pressure
- Low Fuel Flow Alert
- **Emergency Stop**

STS 6004 SPECIFICATIONS

Flow Rate (@60Hz)	4 GPM/240 GPH (15.1 LPM/908 LPH)		
Primary Filter/Water Separator	10 or 30μ Particulate or 60μ Stainless Steel Screen with Centrifugal Water Separator		
Secondary Filter/ Water Block	1, 3, 10 or 25μ Particulate or 3, 10μ Water Block		
Fuel Conditioner	LG-X 1500 Inline Conditioner		
System Controller	Programmable, Fully Automated UL 508A SMART Filtration Controller with BMS/BAS Interface and Digital Text Readout		
Pump	1/3 HP Gear Pump		
Power	120V/60Hz/15A or 230V/50Hz/15A		
Plumbing	Stainless Steel		
Ports	3/4" NPT In 3/4" NPT Out		
Enclosure Cabinet	NEMA 12 (IP55), 13 (IP65), 4 (IP66), and 4X (IP66) Powder Coat or Stainless Steel		
Dimensions	36" x 36" x 12" (H x W x D) (91 x 91 x 30 cm)		
Weight	≈ 290 lbs (131.5 kg)		
Not for use with fluids that have a flash point below 100°F (37.8°C).			

SMART FILTRATION CONTROLLERS:


- Maintenance Alert Log File
- Runtime Totalizer
- Alarm History
- On-Screen Help

ALL STS SYSTEMS FEATURE:

- Multi-stage Water Removal and Particulate Filtration
- NEMA 12,13, 4, 4X Powder Coated or Stainless Enclosure
- **UL508A Smart Filtration Controller**
- Stainless Steel Plumbing







- 1. Fuel Inlet (From Tank)
- 2. Inlet Ball Valve
- 3. WATECT Water Sensor
- 4. Smart Filtration Controller
- 5. Pre Filter/Water Separator
- 6. Water Level Probe
- 7. Leak Detector
- 8. Pump Motor
- 9. AXI Inline LG-X 1500 Conditioner
- 10. Fine Filter/Water Block
- 11. Inline Flow Switch
- 12. Outlet Ball Valve
- 13. Fuel Outlet (Discharge)
- 14. Gear Pump
- 15. Vacuum Switch
- 16. Pressure Switch

STS 6004 OPTIONS:

- AFC 705/710 Fuel Catalyst
- Stainless Steel Enclosure
- Cabinet Heater
- Stand
- Cabinet Color Options

REPLACEMENT FILTER OPTIONS:

Pre Filter	Part No.	Fine Filter	Part No.
10 μ Filter Element	01810	3μ Water Block Filter	WB-3
30μ Filter Element	01830	10μ Water Block Filter	WB-10
60μ Filter Element	01860	1μ Fine Filter	FF-1
		3μ Fine Filter	FFZ-3
		10µ Fine Filter	FF-10

STS SYSTEM INTEGRATION:

